

# Anabec Systems

800.369.8463

[www.Anabec.com](http://www.Anabec.com)



\*Restrictions Apply

## X90

**X90 is a second step in the Anabec System of Products. Application of X90 results in an extremely durable moisture barrier. X90 is applied after cleaning the surface with Advanced Cleaning Solution. This product is appropriate for use on previously cleaned and/or disinfected, unfinished building material surfaces. X90 can serve as a primer for latex paints.**

# X90

### **General Characteristics:**

- Ready to Use
- Surface Penetrant

### **Color:**

- Solid White

### **Coverage:**

- 250-400 sq ft / gallon

Choose the **Anabec System** Better Chemistry. Superior Results.

# X90

## Product Info

Classification  
Key Ingredient(s)

Moisture Barrier  
Latex  
Silver

### Packaging / Storage

Packaged	5 gal
Shelf Life	18 months
Storage Conditions	Do not Freeze Store out of reach of children

### Properties

Finish after applied	Opaque White
Odor	Solvent / Latex
pH	7-9
Viscosity	4,000-10,000 cps
Density	10.2 lbs/gal
Flash Point	>100 C
Est VOC	0.15
Solubility in Water	Soluble

### Application

Dilution	Ready to Use
Coverage	250-400 sq ft
Air Less Sprayer	Yes
Foggable	No
Brush	Yes
Roller	Yes
Dry to touch	2 hours
Dry through	18-24 hours
Clean-up	Water / Soap



# Anabec Systems

[www.Anabec.com](http://www.Anabec.com)

716.759.4006  
toll free: 800.369.8463