



Nash
Distribution

HandiFoam
Foam sealant

High-Performance Insulation & Sealing Solutions

The HandiFoam® line of one-component polyurethane foam sealants is engineered for professionals who demand superior performance in air-sealing, insulating, and fire-blocking applications. From extreme weather conditions to specialized window and door installs, HandiFoam provides a precision seal every time.

ENERGY EFFICIENCY

Creates an airtight thermal barrier for gaps, cracks, and void filling.

ADHESION POWER

Bonds aggressively to wood, metal, masonry, and most plastics.

CLIMATE VERSATILITY

Specialized formulas for "Extreme" cold + "West" (low humidity) environments ensure a full cure where other foams fail.

CONTROLLED EXPANSION

Low-pressure window and door formulas prevent frame distortion and costly call-backs.

II-205 HANDIFOAM CAN

P30002	<ul style="list-style-type: none"> • <i>Single can</i> • Coverage: 1996 linear ft. at 1/4" bead 	\$4.97/ Can
--------	---	-------------

TECHNICAL DATA

- **VOC Content:** 165 g/L (Compliant with high standards)
- **Flash Point:** -104°C (-155°F)
- **Cell Structure:** Closed cell; provides excellent moisture resistance.
- **Shelf Life:** Refer to canister date code for peak performance.

SAFETY & PROPER USAGE

- **Flammability:** Highly flammable. Keep away from ignition sources (sparks/pilot lights).
- **PPE Required:** Wear chemical-resistant gloves (Nitrile), safety goggles, and protective clothing to prevent skin sensitization.
- **Ventilation:** Ensure cross-ventilation during application. If used in confined spaces, an approved respirator is required.
- **Storage:** Store in a cool, dry place. Protect from temperatures above 122°F (50°C)



CONSULT: 800-288-0831 **VISIT:** nashdistribution.com **ENGAGE:** info@nashdistribution.com